

TECHNICAL SHEET

28/11/2025




Commissioning trolley for in-house transportation of window elements. Stable steel construction. Trolley for in-house transportation. Openings for forklift transportation. Four hooks for crane transportation. Four lashing strap attachment points. Profile supports with rubber surface. Castors can be removed for increased stability of the commissioning trolley. Four swivel castors, two of which with locking stop.

1

(someco)


TECHNICAL SHEET

28/11/2025




Removable casters

Casters can be removed for increased stability of the commissioning trolley on the floor. Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



Supports with rubber strip

Supporting surfaces equipped with rubber strips to protect profiles from damage



Lashing strap attachment points

With four lashing strap attachment points



Crane attachment points

Equipped with four crane attachment points



Forklift openings

Equipped with four forklift openings



Lifting station (Optional)

HBR 1600 Lifting station for the transfer of heavy windows to the transport trolley KW 4





28/11/2025



KW 4 / TRANSPORT AND TROLLEYS

DIMENSION AND WEIGHT	
Length (mm)	2.000
Width (mm)	1.000
Height (mm)	1.850
Weight (kg)	150

STORAGE CAPACITY Load capacity (kg) 500

•
4
4
0
4
2
125

Included ● Available ○