



## **SBZ 610/03**

Cutting and machining  
centers



Maximum working speeds with the highest quality are delivered by three cutting units. Automatic cutting centre with three built-in cutting units for cutting profiles to length for window and door manufacturing. Work sequence as needed, either from the left towards the right or the reverse. Infeed with motorised, continuously adjustable gripper. Lifting function for gap-free loading of the feed magazine. Profiles are guided on rollers to ensure gentle treatment of the profile and protective film. Optimised length cutting with no processing waste. Internal gripper avoids damaging the profiles. Integrated measuring sensors for residual piece detection. Outfeed for parts via discharge table. Industrial PC with Windows operating system.

**Voilàp S.p.A.**  
Via Archimede, 10  
41019 - Limidi di Soliera (MO)  
ITALY


Tel 059 895411  
Fax: 059 859404  
P.IVA e C.F. 02057270361  
info@somecopvc.com  
www.somecopvc.com

The right to make technical alterations is reserved.




LAYOUT

Left version (left to right)



Right version (right to left)



- A - Loading magazine
- B - Machining unit
- C - Unloading magazine
- \* - Standard version

The overall dimensions may vary depending on the product configuration.

AXIS TRAVEL

Y AXIS (cross) (mm)	370
Z AXIS (vertical) (mm)	270
X AXIS (bar positioning) (mm)	6.500
Y1 AXIS (cross gripper positioning) (mm)	130
Z1 AXIS (vertical gripper positioning) (mm)	145
A1 AXIS (gripper rotation)	280°

Voilàp S.p.A.  
 Via Archimede, 10  
 41019 - Limidi di Soliera (MO)  
 ITALY

Tel 059 895411  
 Fax: 059 859404  
 P.IVA e C.F. 02057270361  
 info@somecopvc.com  
 www.somecopvc.com

The right to make technical alterations is reserved.



LOADING UNIT: PROFILE POSITIONING

Workpiece reference stop near the working unit	●
Maximum loadable length (mm)	6.500
Belt loading magazine for 10 profiles with a length varying from 500 mm to 6.500 mm	●
Electronically controlled 0 - 360° collet rotation (C1 axis)	●
Minimum machinable profile section - W x H (mm)	30 x 30


BLADE MOTORS (MANUAL CHANGE)

Maximum power rating in S6 (kW)	4
Maximum speed (r.p.m.)	2.850
Air cooling	●
Blade diameter (mm)	550
Number of motors	3

MACHINABLE CUTTING ANGLES

Fixed cutting angle	45° / 90° / 135°
---------------------	------------------

CUTTING DIAGRAM





### WORKPIECE LOCKING

Automatic fixed clamping system before machining area	●
Automatic fixed clamping system after machining area	●
Clamping system standard height 20 mm	●
Clamping system for profile adapted to profile system	○

### MODES OF OPERATION

Cutting PVC Profiles	●
Rotary axis gripper	●

### SUPPORT BASE

Monolithic in electrowelded and standardised steel	●
--	---

### UNLOADING UNIT

Unloading table with a pneumatic pusher for workpieces of up to 4000 mm	●
Belt magazine unloading depth (mm)	1.900

### ELECTRIC CABINET COOLING

Electrical cabinet with air conditioner for operating temperature < 45 °C	●
Electrical panel and CN conditioner for operating temperatures < 50°C	○

Included ● Available ○